

JQuery Validator <http://docs.jquery.com/Plugins/Validation>

`$(form selector).validate(options);`

Rules

`$(".selector").validate({`

`rules: {`

`name: { required: true},`

`email: { required: true, email: true }`

`}`

`});`

required	true/false
email	true/false
digits	True/false
creditcard	True/false
min	Numeric
max	Numeric

minlength	Numeric
maxlength	Numeric
Rangelength	Numeric, ex. rangelength: [2, 6]
url	True/false
date	True/false
dateISO	True/False
dateDE	True/false (German Date)
phoneUS	True/false
number	True/false
numberDE	True/false (German Date)
accept	Ex: "xls csv" (file types)
equalTo(other)	String, ex: "#password"
remote	String/options – see \$.ajax for options

Messages

You can create special messages for each rule type.

`$(".selector").validate({ rules: {...},`

`messages: {`

`name: "Please specify your name",`

`email: { required: "Please enter your email address", email: "Please enter a valid email address"}`

`}});`

Validator Option callbacks

submitHandler(form)	success(element)
invalidHandler(form, validator)	highlight(element, errorClass)
errorPlacement(error, element)	unhighlight(element)

Validator Option properties

debug: bool	ignore: selector	rules: {}	messages: {}
groups: {}	onsubmit: bool	onfocusout: bool	onkeyup: bool
onclick: bool	focusInvalid: bool	focusCleanup: bool	Meta: string
errorClass: "error"	validClass: "valid"	errorElement: "label"	wrapper: "li"
errorLabelContainer:	errorContainer	success: "valid"	ignoreTitle: bool

Validator Plugin Methods

validate(options)	valid()	rules()	rules("add", rules)
rules("remove", rules)	removeAttrs(attr)		

Validator Methods

form()	element(element)	addClassRules(name, Rules)	showErrors(errors)
numberOfInvalids()	resetForm()	addMethod(name, method, message)	setDefaults(defaults)

JQuery Custom Selectors:

:blank, :filled, :unchecked